



#### **Description:**

PRO-TSF-207 Server/Network Cabinets are designed to meet various storage demands, guarantee maximum data security and protection, and protect computers, routers, modems, and other devices in space-saving. Network Cabinet adopts ventilated or removable panel design that allows generous airflow to keep equipment operating safely.

Configuration for standard racks is welded frame integrated with side panels and vented top cover with fan mounting provision, while toughened glass door & hexagonal reticular high-density vented door, Network Cabinet are available from 18U to 42U Variants with 600mm, 800mm, and 1000mm deep configurations.



### Feature:

Exquisite design with precise dimension and craftsmanship;

Toughened glass front door with obliquely vented door border and three-section vented rear door;

Hexagonal reticular high-density vented front door & rear door for protection, ventilation, and reliable operation;

Blue Zinc Mounting Profiles, free of static

Adjustable feet and heavy-duty castors are available simultaneously;

Optional installation of the plinth to enable cabinets fixation, under-base cable entry/ventilation;

Efficient and reliable cabinet connection by baying kit.

Removable side panels to ease maintenance.

Around 1/3 assembled original volume when the flat pack.

#### Main Parts :

No.	Component Name	Quantity	Unit	Material	Surface Finish	Remark
1	Top Cover	1	рс	SPCC cold rolled steel T1.0	Powder Coated	
2	Fun Unit	1	рс		Powder Coated	With 2 fans
3	Mounting Profile	4	рс	SPCC cold rolled steel T2.0 Powder Coated		
4	Mount Angle	6	рс	SPCC cold rolled steel T1.2 Powder Coated		4 pcs for lower 30U
5	Frame	2	рс	SPCC cold rolled steel T1.0 Powder Coated		
6	Spring Lock	1	рс		Black	
7	Toughened Glass Front Door	1	рс	Tempered glass	Powder Coated	
8	Side Panel	2	рс	SPCC cold rolled steel T1.0	Powder Coated	Removable
9	Bottom Panel	1	рс	SPCC cold rolled steel T1.0	Powder Coated	
10	Small Round Lock	1	рс		Nickel Coated	
11	Steel Rear Door	1	рс	SPCC cold rolled steel T1.0	Powder Coated	
12	M6 Philip-head Screw	20	рс	Steel	Color Zinc Coated	4 pcs for lower 30U
13	M6 Square Nut	20	рс	Steel	Color Zinc Coated	4 pcs for lower 30U
14	Castor	4	рс			
15	M12 Adjustable feet	4	рс			



Color :

RAL9004	Black	
RAL7035	Gray	

## Standard:

Comply with ANSI/EIA RS-310-D、IEC297-2、DIN41494; PART1、DIN41494; PART7、ETSI standard.

# Order Info :

Model No.	Capacity (RU)	Width (mm)	Depth (mm)	Whole Packing Volume (W*D*H)	Flat Packing Volume (CBM)
PRO-TSF-207A1			600	630*630*1008	0.2524
PRO-TSF-207A2	18	600	800	630*830*1008	0.2524
PRO-TSF-207A3			900	630*930*1008	0.2799
PRO-TSF-207A4			1000	630*1030*1008	0.2864
PRO-TSF-207B1			600	630*630*1176	0.3055
PRO-TSF-207B2	22	600	800	630*830*1176	0.3019
PRO-TSF-207B3			900	630*930*1176	0.3213
PRO-TSF-207B4			1000	630*1030*1176	0.3392
PRO-TSF-207C1			600	630*630*1403	0.3320
PRO-TSF-207C2	27	600	800	630*830*1403	0.3623
PRO-TSF-207C3			900	630*930*1403	0.3823
PRO-TSF-207C4			1000	630*1030*1403	0.4048
PRO-TSF-207D1			600	630*630*1625	0.3757
PRO-TSF-207D2	32	600	800	630*830*1625	0.4227
PRO-TSF-207D3			900	630*930*1625	0.4451
PRO-TSF-207D4			1000	630*1030*1625	0.4759
PRO-TSF-207E1			600	630*630*1848	0.4318
PRO-TSF-207E2		600	800	630*830*1848	0.4642



PRO-TSF-207E3			900	630*930*1848	0.4746
PRO-TSF-207E4	37		1000	630*1030*1848	0.4935
PRO-TSF-207E5			600	830*630*1848	0.4423
PRO-TSF-207E6		800	800	830*830*1848	0.4759
PRO-TSF-207E7			900	830*930*1848	0.5056
PRO-TSF-207E8			1000	830*1030*1848	0.4867
PRO-TSF-207F1			600	630*630*2070	0.4951
PRO-TSF-207F2	42	600	800	630*830*2070	0.4998
PRO-TSF-207F3	]		1000	630*1030*2240	0.5595